

sLED
by **Switch Lighting**











SSWS310

Stair / wall lighting

SSWS320


Stair / wall lighting


Scan to view website

Wall / stair light

Lighting excellence for every space

- stylish & safe stair lighting
- compact size
- flicker-free, non-dimming driver included
- optional dimming driver
- IP54 front
- constant current (Max 350mA)





Options

Beam angle

60˚

CRI

CRI 80

CCT

2700K 3000K

Trim colour

Textured White RAL9003

Optional power supply – constant current

Ordered separately

230VAC circuit (@350mA) only 2700K, 3000K, 4000K

1-4 lights	non-dimming Mini 350mA power supply
1-3 lights	TE dimmable SE-9-350-700
3-11 lights	TE dimmable SE-12-100-400
3-13 lights	TE dimmable SE-15-350-700
3-13 lights	dimmable SE-40-300-1050* (5-19 R, 3-12 G)

12 or 24VDC circuit – all types:

1-3 lights	LDD-350LW @ 12V
1-7 lights	LDD-350LW @ 24V

Scan to view driver options

Product information

Example: 3000K

Contact Switch Lighting for data of other variants

CCT (K)	LED Power (W)	Delivered lumens (lm)	Insulation coverable NZ	AU	UK/EU
3000	1	80	ICF	IC4	√

Size 55x22mm | Cut-out Ø48-49mm | Hole depth >32mm | IP54 Front

how to specify SSWS310

Please confirm model option availability from our website.

e.g. code = SSWS310-30-TW

Model	–	CCT	–	Trim Colour	–	Market
SSWS310 SSWS320		27 = 2700K 30 = 3000K		TW = Textured White (RAL9003)		= NZ 1 = Aust 2 = UK 3 = EU

Please see **www.switch-lighting.co.nz** for specifications, lux levels, SDoCs, ies files and installation instructions.

Warranty 5 Years

L70 (40,000 h)

IC-F ABUTTED & COVERED

IC-4

CONSTANT CC CURRENT

RoHS