

## Non-coverable drivers.

**LO5020** - 12W 350mA or 700mA constant current mains driver



Type	Constant current
Max power output	12W
Dimmable	No
Size	99 x 39 x 23 mm
Power factor	0.9
Input voltage	110-240VAC 50/60Hz
Current output	Output 1: 350mA (1-9 LED) Output 2: 700mA (1-5 LED)
Voltage output	3 - 32VDC
Ambient temperatures (ta)	-20 to +50°C
Max temp (tc)	85°C



**LO5021** - 12W 350mA or 700mA dimmable constant current mains driver



Type	Constant current
Max power output	12W
Dimmable	Yes - trailing edge dimmer
Size	99 x 39 x 23 mm
Power factor	0.9
Input voltage	230-240VAC 50/60Hz
Current output	Output 1: 350mA Output 2: 700mA
Voltage output	3 - 32VDC
Ambient temperatures (ta)	-20 to +45°C
Max temp (tc)	85°C



**LO5049** - 40W 245-1050mA 60VDC



Type	Constant current
Max power output	40W
Dimmable	1-10V (range 15-100%) / photometer (100k log b)
Size	157 x 42 x 32 mm
Power factor	0.98 @ 230V
Input voltage	110-240VAC 50/60Hz
Current output	245mA to 1050mA
Voltage output	22 - 60VDC
Ambient temperatures (ta)	-20 to +60°C
Max temp (tc)	80°C



**IE-12D** - 12W 180-500mA Dali Dimming Mains Driver



Type	Constant current
Max power output	12W
Dimmable	Dali-2 1-100%
Size	119 x 52 x 22.5mm
Power factor	0.95
Input voltage	220-240VAC 50/60Hz
Current output (switchable)	180 - 500mA
Voltage output	Varies
Ambient temperatures (ta)	-25 to 50°C
Max temp (tc)	80°C



**MINI 350mA IP65** - Driver  
**MINI 700mA IP65** - Driver



Type	Mini 350mA	Mini 700mA
Type	Constant current	Constant current
Max power output	4W	4W
Dimmable	No	No
Size	38 x 27 x 21mm	38 x 27 x 21mm
Power factor	0.4	0.4
Input voltage	100-240VAC 50/60Hz	100-240VAC 50/60Hz
Current output	350mA	700mA
Voltage output	3 - 12VDC	3 - 6VDC
Ambient temps (ta)	-20 to +50°C	-20 to +50°C
Max temp (tc)	80°C	80°C



**CL350D-240-C** - 17W 350mA DALI Dimming Mains Driver  
**CL500D-240-C** - 24W 500mA DALI Dimming Mains Driver



Type	CL350D-240-C	CL500D-240-C
Type	Constant current	Constant current
Max power output	17W	24W
Dimmable	Dali dimming - off, 10%-100%	Dali dimming - off, 10%-100%
Size	180 x 32 x 32 mm	180 x 32 x 32 mm
Power factor	0.96	0.96
Input voltage	220-240VAC 50Hz	220-240VAC 50Hz
Current output	350mA	500mA
Voltage output	15 - 48V	15 - 48V
Ambient temps (ta)	-25 to +50°C	-25 to +50°C
Max temp (tc)	80°C	80°C



**MINI LDD350LW** - 12-36VDC input constant current Driver



Type	Constant current
Max power output	8W
Dimmable	Yes via PWM
Size	22 x 10 x 9 mm
Power factor	n/a
Input voltage	9 - 36VDC
Current output	350mA (700mA option)
Voltage output	2 - 32VDC
Ambient temperatures (ta)	-40 to +70°C



**MINI LDB-300LW** - 12-36VDC input constant current Driver



Type	Constant current
Max power output	12W
Dimmable	Yes via PWM
Size	32 x 20 x 12 mm
Power factor	n/a
Input voltage	9 - 36VDC
Current output	300mA
Voltage output	2 - 40VDC
Ambient temperatures (ta)	-40 to +70°C



**Q4-12V-20W** - 20W 12VDC Power Supply



Type	Constant voltage
Max power output	20W
Dimmable	No
Size	113 x 44 x 28 mm
Power factor	0.8
Input voltage	220-240VAC 50Hz
Current output	00-1.7A
Voltage output	12VDC
Ambient temperatures (ta)	-20 to +50°C
Max temp (tc)	80°C



**SLDV-12V-40W** - 40W 12VDC Power Supply  
**SLDV-12V-75W** - 75W 12VDC Power Supply



	SLDV-12V-40W	SLDV-12V-75W
Type	Constant voltage	Constant voltage
Max power output	40W	75W
Dimmable	No	No
Size	176 x 58 x 30.5 mm	186 x 64 x 39 mm
Power factor	0.95	0.95
Input voltage	100-240V	100-240V
Current output	0-3.3A	0-6.25A
Voltage output	12VDC	12VDC
Ambient temperatures (ta)	-20 to +50°C	-20 to +50°C
Max temp (tc)	80°C	80°C



**SLDV-24V-40W** - 40W 24VDC Power Supply  
**SLDV-24V-75W** - 75W 24VDC Power Supply  
**SLDV-24V-150W** - 150W 24VDC Power Supply



	SLDV-24V-40W	SLDV-24V-75W	SLDV-24V-150W
Type	Constant voltage	Constant voltage	Constant voltage
Max power output	40W	75W	150W
Dimmable	No	No	No
Size	176 x 58 x 30.5 mm	186 x 64 x 39 mm	191 x 70 x 40 mm
Power factor	0.95	0.95	0.95
Input voltage	100-240V	100-240V	100-240V
Current output	0-1.65A	0-3.15A	0-6.3A
Voltage output	24VDC	24VDC	24VDC
Ambient temperatures (ta)	-20 to +50°C	-20 to +50°C	-20 to +50°C
Max temp (tc)	80°C	80°C	80°C

